

Leica Viva GS16

Data sheet



Engaging software

The Leica Viva GS16 GNSS smart antenna is accompanied with the revolutionary Captivate software, turning complex data into the most realistic and workable 3D models. With easy-to-use apps and familiar touch technology, all forms of measured and design data can be viewed in all dimensions. Leica Captivate spans industries and applications with little more than a simple swipe, regardless of whether you work with GNSS, total stations or both.



Infinitely bridging the field to the office

Leica Infinity imports and combines data from your GNSS, total station and level instruments for one final and accurate result. Processing has never been made easier when all your instruments work in tandem to produce precise and actionable information.

ACC»

Customer care only a click away

Through Active Customer Care (ACC), a global network of experienced professionals is only a click away to expertly guide you through any challenge. Eliminate delays with superior technical service, finish jobs faster and avoid costly site revisits with excellent consultancy support. Control your costs with a tailored Customer Care Package (CCP), giving you peace of mind you are covered anywhere, anytime.

Leica Viva GS16

GNSS TECHNOLOGY

Self-learning GNSS	Leica RTKplus SmartLink (worldwide correction service) SmartLink fill (worldwide correction service)	Adaptive on-the-fly satellite selection Remote precise point positioning (3 cm 2D) ¹ Initial convergence to full accuracy typically 18 min, Re-convergence < 1 min Bridging of RTK outages up to 10 min (3 cm 2D) ¹
Leica SmartCheck	Continuous check of RTK solution	Reliability 99.99%
Signal tracking	GPS GLONASS Galileo BeiDou QZSS NavIC SBAS L-Band	L1, L2, L2C, L5 L1, L2, L2C, L3 E1, E5a, E5b, AltBOC, E6 B1I, B1C, B2I, B2a, B3I L1, L2C, L5, L6 ² L5 ³ WAAS, EGNOS, MSAS, GAGAN Terrastar
Number of channels		555 (more signals, fast acquisition, high sensitivity)

MEASUREMENT PERFORMANCE & ACCURACY¹

Time for initialisation		Typically 4 s
Real-time kinematic (Compliant to ISO17123-8 standard)	Single baseline Network RTK	Hz 8 mm + 1 ppm / V 15 mm + 1 ppm Hz 8 mm + 0.5 ppm / V 15 mm + 0.5 ppm
Post processing	Static (phase) with long observations Static and rapid static (phase)	Hz 3 mm + 0.1 ppm / V 3.5 mm + 0.4 ppm Hz 3 mm + 0.5 ppm / V 5 mm + 0.5 ppm
Code differential	DGPS / RTCM	Hz 25 cm V 50 cm

COMMUNICATIONS

Communication ports	Lemo Bluetooth®	USB and RS232 serial Bluetooth® v2.00 + EDR, class 2
Communication protocols	RTK data protocols NMEA output Network RTK	Leica, Leica 4G, CMR, CMR+, RTCM 2.2, 2.3, 3.0, 3.1, 3.2 MSM NMEA 0183 V 4.00 & v 4.10 and Leica proprietary VRS, FKP, iMAX, MAC (RTCM SC 104)
Built-in data links	3.75G GSM / UMTS / CDMA phone modem Radio modem	Fully integrated, internal antenna Fully integrated, receive and transmit, external antenna 403 - 473 MHz, 1 W output power, up to 28800 bps over air
External data links		GSM / GPRS / UMTS / CDMA and UHF / VHF modem

GENERAL

Field controller and software	Leica Captivate software	Leica CS20 field controller, Leica CS30 & CS35 tablets
User interface	Buttons and LEDs Web server	On / Off and Function button, 7 status LEDs Full status information and configuration options
Data recording	Storage Data type and recording rate	Removable microSD card Leica GNSS raw data and RINEX data at up to 20 Hz
Power management	Internal power supply External power supply Operation time ⁴	Exchangeable Li-Ion battery (2.6 Ah / 7.4 V) Nominal 12 V DC, range 10.5 - 28 V DC 7 h receiving (Rx) data with internal radio, 5 h transmitting (Tx) data with internal radio, 6 h Rx / Tx data with internal phone modem
Weight and dimensions	Weight Diameter x Height	0.93 kg / 3.20 kg standard RTK rover setup on pole 190 mm x 90 mm
Environmental	Temperature Drop Proof against water, sand and dust Vibration Humidity Functional shock	-40 to 65°C operating, -40 to 80°C storage Withstands topple over from a 2 m survey pole onto hard surfaces IP68 (IEC60529 / MIL STD 810G 506.5 I / MIL STD 810G 510.5 I / MIL STD 810G 512.5 I) Withstands strong vibration (ISO9022-36-08 / MIL STD 810G 514.6 Cat.24) 100% (ISO9022-13-06 / ISO9022-12-04 / MIL STD 810G 507.5 I) 40 g / 15 to 23 msec (MIL STD 810G 516.6 I)

LEICA VIVA GS16 - GNSS SMART ANTENNA

SUPPORTED GNSS SYSTEMS

	Performance	Unlimited
Multi-frequency	✓	✓
GPS / GLONASS / Galileo / BeiDou / QZSS	✓ / • / • / • / •	✓ / ✓ / ✓ / ✓ / ✓

RTK PERFORMANCE

DGPS/RTCM, RTK Unlimited, Network RTK	✓	✓
SmartLink fill / SmartLink	• / •	✓ / •

POSITION UPDATE & DATA RECORDING

20 Hz positioning	✓	✓
Raw data / RINEX data logging / NMEA out	✓ / • / •	✓ / ✓ / ✓

ADDITIONAL FEATURES

RTK reference station functionality	✓	✓
3.75G or CDMA Phone / UHF Radio (receive & transmit) modem	• / •	• / •

✓ Standard • Optional

¹ Measurement precision, accuracy, reliability and time for initialisation are dependent upon various factors including number of satellites, observation time, atmospheric conditions, multipath etc. Figures quoted assume normal to favourable conditions. A full BeiDou and Galileo constellation will further increase measurement performance and accuracy.

² QZSS L6 will be provided through future firmware upgrade.

³ Support of NavIC L5 is incorporated and will be provided through future firmware upgrade.

⁴ Might vary with temperature, age of battery, transmit power of data link device.

The Bluetooth® trademarks are owned by Bluetooth SIG, Inc. Illustrations, descriptions and technical data are not binding. All rights reserved. Printed in Switzerland - Copyright Leica Geosystems AG, Heerbrugg, Switzerland, 2021. 845114en - 04.21

Leica Geosystems AG
www.leica-geosystems.com



- when it has to be right

